



**CASWELL INC**

## **Safety Data Sheet Gas Tank Sealer Part A**

---

### **SECTION 1: Identification**

#### **1.1 Product identifier**

Product name	Gas Tank Sealer Part A
Product number	GTSA
Brand	Caswell
Substance name	Epoxy resin
CAS no.	28064-14-4

#### **1.2 Other means of identification**

Dragon's Blood, Black Magic, Petrol Blue, Battleship Grey, Royal Blue

#### **1.4 Supplier's details**

Name	Caswell Inc
Address	7696 Route 31 Lyons, NY 14489 USA
Telephone	315 946 1213
Fax	315 946 4456
email	sales@caswellplating.com

PRODUCT SUPPLIED IN AUSTRALIA  
BY  
CASWELL AUSTRALIA  
Factory 1, 51 Elm Park Drive Hoppers  
Crossing  
Victoria, 3029  
Phone 03 9741 7103  
Emergency 000  
All hours 0427 70 80 90

#### **1.5 Emergency phone number(s)**

Office Hours (9-4ET): 315 946 1213  
24 Hour: CHEMTEL US# 1-800-255-3924    Intl# +01-813-248-0585

---

### **SECTION 2: Hazard identification**

#### **2.1 Classification of the substance or mixture**

- Skin corrosion/irritation (chapter 3.2), Cat. 2
- Eye damage/irritation (chapter 3.3), Cat. 2A
- Sensitization, skin (chapter 3.4), Cat. 1
- Hazardous to the aquatic environment - long-term hazard (chapter 4.1), Cat. 2

#### **2.2 GHS label elements, including precautionary statements**

**Pictogram**

# Safety Data Sheet

## Gas Tank Sealer Part A



### Signal word

### Warning

#### Hazard statement(s)

H315  
H319  
H317  
H411

Causes skin irritation  
Causes serious eye irritation  
May cause an allergic skin reaction  
Toxic to aquatic life with long lasting effects

#### Precautionary statement(s)

P264  
P280  
P302+P352  
P321  
P332+P313  
P362+P364  
P305+P351+P338  
  
P337+P313  
P261  
P272  
P333+P313  
P501  
P273  
P391

Wash ... thoroughly after handling.  
Wear protective gloves/protective clothing/eye protection/face protection.  
IF ON SKIN: Wash with plenty of water/...  
Specific treatment (see ... on this label).  
If skin irritation occurs: Get medical advice/attention.  
Take off contaminated clothing and wash it before reuse.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/attention.  
Avoid breathing dust/fume/gas/mist/vapours/spray.  
Contaminated work clothing should not be allowed out of the workplace.  
If skin irritation or a rash occurs: Get medical advice/attention.  
Dispose of contents/container to ...  
Avoid release to the environment.  
Collect spillage.

---

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Substance name	Epoxy resin
CAS no.	28064-14-4
Formula	C10H12O3
Other names / synonyms	Phenol, polymer with formaldehyde, glycidyl ether; Epoxy resin

---

## SECTION 4: First-aid measures

### 4.1 Description of necessary first-aid measures

If inhaled	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
------------	---

# Safety Data Sheet

## Gas Tank Sealer Part A

In case of skin contact	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
In case of eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
If swallowed	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband
Personal protective equipment for first-aid responders	See section 8

### 4.3 Indication of immediate medical attention and special treatment needed, if necessary

No specific treatment. Treat symptomatically. Call medical doctor or poison control center immediately if large quantities have been ingested.

---

## SECTION 5: Fire-fighting measures

### 5.1 Suitable extinguishing media

Use an extinguishing agent suitable for the surrounding fire

### 5.2 Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

## **SECTION 6: Accidental release measures**

### **6.3 Methods and materials for containment and cleaning up**

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

---

## **SECTION 7: Handling and storage**

### **7.1 Precautions for safe handling**

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

---

## **SECTION 8: Exposure controls/personal protection**

### **8.2 Appropriate engineering controls**

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

### **8.3 Individual protection measures, such as personal protective equipment (PPE)**

#### **Pictograms**



#### **Eye/face protection**

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

#### **Skin protection**

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be

## Safety Data Sheet

### Gas Tank Sealer Part A

different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): butyl rubber, Ethyl Vinyl Alcohol Laminate (EVAL)

#### Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Respiratory protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator

#### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

---

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

Appearance/form (physical state, color, etc.)	Gray Liquid
Odor	Slight
Odor threshold	Not available.
pH	6
Melting point/freezing point	Not available.
Initial boiling point and boiling range	>200 deg C
Flash point	Closed Cup > 200 deg C
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability limits	Not available.
Vapor pressure	<0.0001 kPa
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	insoluble
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	> 200 deg C
Viscosity	Not available.
Explosive properties	Not available.
Oxidizing properties	Not available.

#### Other safety information

Product does not contain Volatile Organic Compounds

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not available.

# Safety Data Sheet

## Gas Tank Sealer Part A

### 10.2 Chemical stability

Stable

### 10.3 Possibility of hazardous reactions

Not available.

### 10.4 Conditions to avoid

Not available.

### 10.5 Incompatible materials

Not available.

### 10.6 Hazardous decomposition products

Not available.

---

## SECTION 11: Toxicological information

### Information on toxicological effects

#### Acute toxicity

Bisphenol F epoxy resin

LD50 Dermal

Rat - Male, Female >2000 mg/kg

#### Skin corrosion/irritation

Bisphenol F epoxy resin

OECD 405 Acute Eye Irritation/

Corrosion Rabbit Eyes - Non-irritant.

#### Carcinogenicity

None

#### Reproductive toxicity

None

#### STOT-single exposure

Not Available

#### STOT-repeated exposure

Not Available

#### Aspiration hazard

Not Available

---

## SECTION 12: Ecological information

### Toxicity

Bisphenol F epoxy resin

OECD 201 Alga, Growth Inhibition Test

Acute EC50 72 hours Static

Algae

1.8 mg/l

# Safety Data Sheet

## Gas Tank Sealer Part A

---

### SECTION 13: Disposal considerations

#### Disposal of the product

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

---

### SECTION 14: Transport information

#### DOT (US)

Not dangerous goods

#### IMDG

Not dangerous goods

#### IATA

Not dangerous goods

---

### SECTION 15: Regulatory information

#### HMIS Rating

Epoxy resin	
HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION	

#### NFPA Rating



---

### SECTION 16: Other information

#### 16.1 Further information/disclaimer

DISCLAIMER: The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own

## **Safety Data Sheet**

### **Gas Tank Sealer Part A**

investigation to determine the suitability of information for their particular purposes. In no event shall Caswell Inc be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, whatsoever arising, even if Caswell Inc has been advised of the possibility of such damages.